

CONTACT MODEL: POPOVJKR

Velocities:

$$\bar{v}_{rel} = \bar{v}_2 - \bar{v}_1 + \bar{\omega}_1 \times \bar{r}_c - \bar{\omega}_2 \times \bar{r}_{c2}$$

$$\bar{v}_{rel,n} = \bar{r}_n \cdot (\bar{r}_n \cdot \bar{v}_{rel})$$

$$\bar{v}_{rel,t} = \bar{v}_{rel} - \bar{v}_{rel,n}$$

Additional parameters:

$$\gamma_{12} = \sqrt{\gamma_1 \gamma_2}$$

$$R^* = \frac{r_1 \cdot r_2}{r_1 + r_2}$$

$$M^* = \frac{m_1 \cdot m_2}{m_1 + m_2}$$

Normal force:

$$s_{crit}^{adh} = \left[\frac{3(\pi \gamma_{12})^2 R^*}{64(E^*)^2} \right]^{\frac{1}{3}}$$

$$F_{crit}^{adh} = \frac{3}{2} \gamma_{12} \pi R^*$$

$$F_n^{JKR-Popov} = F_{crit}^{adh} \cdot \left[-1 + 0.12 \left(\frac{\xi_n}{s_{crit}^{adh}} + 1 \right)^{\frac{5}{3}} \right] \\ - \bar{r}_n \cdot \text{sgn}(\bar{v}_{rel,n} \cdot \bar{r}_n) \cdot 1.8257 \cdot \alpha \cdot |\bar{v}_{rel,n}| \cdot \sqrt{k_n \cdot M^*}$$

Tangential force:

$$\Delta \bar{\xi}_t = \bar{v}_{rel,t} \cdot \Delta t$$

$$k_t = 8 \cdot G^* \cdot \sqrt{R^* \cdot \xi_n}$$

$$\Delta \bar{F}_t = [k_t \cdot \Delta \bar{\xi}_t - 1.8257 \cdot \alpha \cdot \bar{v}_{rel,t} \cdot \sqrt{k_t \cdot M^*}]$$

$$\bar{F}_{t,pr}^{cor} = \bar{F}_{t,pr} - \bar{r}_n \cdot (\bar{r}_n \cdot \bar{F}_{t,pr})$$

$$\bar{F}_{t,pr}^{cor} = \bar{F}_{t,pr} \cdot |\bar{F}_{t,pr}| / |\bar{F}_{t,pr}^{cor}|$$

$$\bar{F}_t = \bar{F}_{t,pr}^{cor} + \Delta \bar{F}_t$$

if

$$|\bar{F}_t| > \mu_{sl} \cdot |\bar{F}_n|$$

then

$$\bar{F}_t = \mu_{sl} \cdot |\bar{F}_n| \cdot \frac{\bar{F}_t}{|\bar{F}_t|}$$

Rolling friction:

$$\bar{M}_{ro,1} = -\mu_{ro} \cdot |\bar{F}_n| \cdot r_1 \cdot \frac{\bar{\omega}_1}{|\bar{\omega}_1|}$$

$$\bar{M}_{ro,2} = -\mu_{ro} \cdot |\bar{F}_n| \cdot r_2 \cdot \frac{\bar{\omega}_2}{|\bar{\omega}_2|}$$

Summarized forces and moments acting on particle:

$$\bar{F}_{tot} = \bar{F}_n + \bar{F}_t$$

$$\bar{F}_1 = \bar{F}_n + \bar{F}_t$$

$$\bar{F}_2 = -\bar{F}_n - \bar{F}_t$$

$$\bar{M}_{tot,1} = \bar{r}_n \times \bar{F}_t \cdot r_1 + \bar{M}_{ro,1}$$

$$\bar{M}_{tot,2} = -\bar{r}_n \times \bar{F}_t \cdot r_2 + \bar{M}_{ro,2}$$

Literature

This model is a part of current research work – results will be published.

Symbol	Description
$\Delta \bar{\xi}_t$	Tangential displacement in the current step [m]
CP	Contact point [m]
γ	Surface tension [-]
\bar{F}_n, \bar{F}_t	Force in normal and tangential directions [N]
$\bar{F}_{t,pr}$	Tangential force on previous iteration [N]
G^*	Equivalent shear modulus [Pa]
\bar{M}_{ro}	Moment due to the rolling friction [N]
m_1, m_2	Particle masses [kg]
M^*	Equivalent mass [kg]
O_1, O_2	Centers of contact partners [m]
μ_{ro}, μ_{sl}	Coefficient of rolling friction and sliding friction [-]
\bar{v}_{rel}	Relative velocity [m/s]
\bar{v}_1, \bar{v}_2	Velocities of contact partners [m/s]
r_1, r_2	Particle radii [m]
R^*	Equivalent radius [m]
\bar{r}_c	Contact vector [m]
\bar{r}_n	Normalized contact vector [-]
$\bar{\omega}_1, \bar{\omega}_2$	Rotation velocities of particles [rad/s]
ξ_n	Normal overlap [m]